

BLANK PAGE



Indian Standard

SMALL TOOLS — HUB TYPE GEAR SHAPER CUTTERS — SPECIFICATION

भारतीय मानक

भौजार — हब टाइप के गियर ब्राकृतिकार कर्तक — विशिष्टि

UDC 621.914.6:621.833

© BIS 1989

BUREAU OF INDIAN STANDARDS MANAK BHAVAN, 9 BAHADUR SHAH ZAFAR MARG NEW DELHI 110002

FOREWORD

This Indian Standard was adopted by the Bureau of Indian Standards on 13 February 1989, after the draft finalized by the Small Tools Sectional Committee had been approved by the Mechanical Engineering Division Council.

In the preparation of this standard, considerable assistance has been derived from DIN 1826: 1977 'Pinion type cutter for cylindrical gears, extended hub gear cutter for spur gear', issued by the Deutsches Institut für Normung.

Indian Standard

SMALL TOOLS — HUB TYPE GEAR SHAPER CUTTERS — SPECIFICATION

1 SCOPE

1.1 This standard covers the dimensions and other requirements of hub type gear shaper cutters suitable for module 1 to 8 mm conforming to IS 2535: 1978 'Basic rack and modules of cylindrical gears for general engineering and heavy engineering (second revision)'.

2 REFERENCES

2.1 The following Indian Standards are necessary adjuncts to this standard:

IS No.

Title

IS 2102 (Part 1): General tolerances for dimensions and form and position: Part 1 General tolerances for linear and angular dimensions (second revision)

IS 7291: 1981

Specification for high speed tool steel (first revision)

IS 7778: 1975

Methods for sampling small

tools

IS 8731: 1978

Technical supply conditions for general purpose gear hobs

3 DIMENSIONS

3.1 Dimensions of hub type gear shaper cutters shall be as given in Tables 1 to 4, read with Fig. 1.

3.2 Tolerances

3.2.1 Class of accuracy and tolerances for cutters shall be according to 'Indian Standard Gear

shaper cutter — Class of accuracy and tolerance (under preparation)'.

NOTE — Till such time the standard under preparation is published, the requirement shall be as agreed to bet-ween the purchaser and the supplier.

3.2.2 For dimension where tolerance has not been specified, tolerance of medium series of IS 2102 (Part 1): 1980 shall apply.

4 MATERIAL

4.1 Gear shaper cutter shall be of high speed tool steel of designation XT91W6 CoMo 5Cr4V2 in accordance with IS 7291: 1981, or equivalent as agreed between the manufacturer and the user.

5 HARDNESS

5.1 Depending upon the choice of the high speed steel, hardness shall be between 820 to 900 HV measured on a flat surface.

6 GENERAL REQUIREMENTS

- 6.1 All sharp corners except the cutting edges shall be removed.
- 6.2 Profile of gear shaper cutters shall be according to 'Indian Standard Reference profiles for gear cutting tools for involute teeth according to IS 2535: 1978 (under preparation)'.

NOTE - Till such time the standard on profile of gear shaper cutters is published, IS 8731: 1978 shall be referred.




Fig. 1 DIMENSIONS FOR HUB Type GEAR SHAPER CUTTER

Table 1 General Plan for Hub Type Gear Shaper Cutters

(Clause 3.1 and Fig. 1) All dimensions in millimetres.

	Nomi	al Diameter (= pitch circle dia	meter. do)
m	75	<u> </u>	125
		Number of teeth Zo	
1	76	100	
1.125	66	88	
1.25	61	80	
1.375	54	72	
1.2	51	68	
1.75	43	58	
2	38	50	64
2.25	34	45	
2.5	32	40	50
2.75	28	36	
3	25	33	42
3.5	22	29	
4	19	25	32
4.5		22	
5	16	20	26
5 5		18	
6			22
7.	=	17	18
8			16
Bore diameter d ₃	31.745	31.745	31.745
	•	or I	or
		44:450	44.450
Table	2	3	4

Table 2 Dimensions for Hub Type Gear Shaper Cutter — Nominal Diameter 75.

(Clause 3 and Fig. 1)

All dimensions in millimetres.

m	z_0	d_0	b ₁ , Min	b ₂ , Min	b ₂ , Min	b ₄ , Min	<i>d</i> ₁	d ₂	H_3
1	76	76		12	10	1	68		
1.125	66	74 25	41	14	12	9	65	50	
1.25	61	76.25					68	ĺ	
1.375	54	74:25		15	13				
1.2	51	76.5	41	17	14	9	65	50	
1.75	43	75.25							
2	38	76	1		1		65	50	31.745
2.25	34	76.5	1 4,	19	16	9			
2.5	32	80	41		İ	1	62	45	
2.75	28	77		21	18		04		
3	25	75				10	CO		
3.5	22	77	43	21	18	1 10	62	45	
4	19	76	46	23	1	12	60		
5	16	80	4 6	25	70	1 14	62	42	

6.3 For the requirements not covered under this standard, reference shall be made to 'Indian Standard Gear shaper cutter — Technical supply conditions (under preparation)'.

NOTE — Till such time the standard under preparation is published, the requirement shall be as agreed to between the purchaser and the supplier.

Table 3 Dimensions for Hub Type Gear Shaper Cutter - Nominal Diameter 100

(Clause 3.1 and Fig. 1)

All dimensions in millimetres.

m	z ₀	d_0	b ₁ , Min	b ₂ , Min	b ₃ , Min	b ₄ . Min	<i>d</i> ₁	d ₂	$\overset{d_{3}}{H_{3}}$
1	100	100		12	10				
1.125	88	96	4 6	14	12	11	90	62	
1 25	80	100					.		
1:375	72	99	40	15	13		00	70	
1.2	68	102	4 6	17	14	11	90	62	
1.75	58	101.2	 ,	19	16			02	
2	50	100	4.0				90		91.745
2.72	4 5	101.25	46	19	16	11	85	62	31·7 4 5 or
2.5	40	100							44.450
2.75	3 6	99	_						
3	33	99	46	23	18	11	85	62	
3.5	23	101-5							
4	25	100					82	Į.	
4.5	22	99	46	23	18	12	80	60	
5	20	100	-20	2.5		1	82 78		
5.5	18	99							
6	17	102	4 6	25	20	12	82	58	

Table 4 Dimensions for Hub Type Gear Shaper Cutter — Nominal Diameter 125

(Clause 3.1 and Fig. 1)

All dimensions in millimetres.

m	Z ₀	<i>d</i> ₀	b ₁ , Min	Min b ₂ ,	b ₃ , Min	t ₄ , Min	d_1	d ₂	д _в Н3
2	64	128		1 22			115	80	
2.5	50	125	48	23	18	12	110		
3	42	126		23				75	
4	32	128		23	18				31.745
5	26	130	48	25	l	12	110	75	or
6	22	132			20				44.450
7	18	126	48	25	20		100		1
-8	16	128	40	30	1 20	12	100	65	Į.

7 PROTECTIVE COATING

7.1 Each gear shaper cutter shall be covered by a suitable rust proofing material and then wrapped in non-absorbent paper.

8 SAMPLING

8.1 The sampling and criteria of acceptance shall be in accordance with IS 7778: 1975.

9 DESIGNATION

9.1 A hub type spur gear shaper cutter, with module 3 mm, nominal diameter 100 mm, bore diameter 44 450 class of accuracy 'A' and reference profile RPI shall be designated as:

Hub Type Gear Shaper Cutter

 $3 \times 100 \times 44 \times A - RPI IS 12537 : 1989.$

10 MARKING

- 10.1 Gear shaper cutters shall be marked with the following information:
 - a) Designation,
 - b) Name of manufacturer or trade mark,
 - c) Module,
 - d) Pressure angle,
 - e) Number of teeth,
 - f) Reference profile, and
 - g) Working depth.

11 PACKING AND PACKAGING

11.1 Each gear shaper cutter or a number of gear shaper cutters of the same type shall be packed in a carton bearing the size, number, designation and manufacturer's name and trade mark.

Standard Mark

The use of the Standard Mark is governed by the provisions of the Bureau of Indian Standards Act, 1986 and the Rules and Regulations made thereunder. The Standard Mark on products covered by an Indian Standard conveys the assurance that they have been produced to comply with the requirements of that standard under a well defined system of inspection, testing and quality control which is devised and supervised by BIS and operated by the producer. Standard marked products are also continuously checked by BIS for conformity to that standard as a further safeguard. Details of conditions under which a licence for the use of the Standard Mark may be granted to manufacturers or producers may be obtained from the Bureau of Indian Standards.

Bureau of Indian Standards

BIS is a statutory institution established under the Bureau of Indian Standards Act, 1986 to promote harmonious development of the activities of standardization, marking and quality certification of goods and attending to connected matters in the country.

Copyright

BIS has the copyright of all its publications. No part of these publications may be reproduced in any form without the prior permission in writing of BIS. This does not preclude the free use, in the course of implementing the standard, of necessary details, such as symbols and sizes, type or grade designations. Enquiries relating to copyright be addressed to the Director (Publications), BIS.

Revision of Indian Standards

Indian Standards are reviewed periodically and revised, when necessary and amendments, if any, are issued from time to time. Users of Indian Standards should ascertain that they are in possession of the latest amendments or edition. Comments on this Indian Standard may be sent to BIS giving the following reference:

Doc: No. EDC 45 (4507)

Amendments Issued Since Publication

Amend No.	Date of Issue	Text Affected

BUREAU OF INDIAN STANDARDS

Headquarters:

Manak Bhavan, 9 Bahad	lur Shah Zalar	Marg, New	Delhi 110002
Telephones: 331 01 31,	331 13 7 5	O-	

Tolognoma . Monal-sanah .

Telephones: 331 of 31, 331 to 73	(Common to all Offices)
Regional Offices:	Telephone
Central: Manak Bhavan, 9 Bahadur Shah Zafar Marg NEW DELHI 110002	331 01 31 331 13 75
Eastern: 1/14 C. I. T. Scheme VII M, V. I. P. Road, Maniktola CALCUTTA 700054	36 24 99
Northern: SCO 445-446, Sector 35-C, CHANDIGARH 160036	{2 18 43 {3 16 41
Southern: C. I. T. Campus, IV Cross Road, MADRAS 600113	41 24 42 41 25 19 41 29 16
Western: Manakalaya, E9 MIDC, Marol, Andheri (East) BOMBAY 400093	6 32 92 95

Branches: AHMADABAD. BANGALORE. BHOPAL. BHUBANESHWAR. GUWAHATI. HYDERABAD. JAIPUR. KANPUR. PATNA.

TRIVANDRUM.